

Control room pedestal SW20-SSP6

Element class 5

- With SSP head
- Top plate with 9 mm wide slots for attaching C-profiles using hammer-head screws M8 x 25 mm (accessories)
- Base plate with perforations diameter of approx. 10.5 mm and 6.6 mm for anchoring to unfinished floors
- Fix in place with Kingspan pedestal fixing adhesive and threaded nut
- Bond to unfinished floors with Kingspan pedestal adhesive



Pedestal	
Pedestal head	Head 120 x 120 x 5 mm Threaded bolt M20 with Hex nut DIN 936 for height adjustment (adjustment range: +/-30 mm) Top plate/threaded bolt circumferential weld
Pedestal base	Pressed-on pedestal tube on embossed base plate Diameter 100 x 2 mm Pedestal tube 24 x 2 mm or 26 x 3 mm

Test results DIN EN 12825:2002	
Element class	≥ 5
Nominal point load	≥ 5 kN
Breaking load	≥ 10 kN
Depending on the respective Kingspan system	

Designation	
SW20 / SSP6	Tube dimensions 24 x 2 mm for PH: 190 to 1,500 mm
SW20 "S" / SSP6	Tube dimensions 26 x 3 mm for PH: 190 to 2,000 mm
Material	Steel, galvanised (transparent/bluish iridescent passivated)
The adjustment ranges mentioned must be observed	



Kingspan Access Floors GmbH

Zum Stadion 4, 63808 Haibach, Germany

T: +49 (0) 6021 63949-0 E: KDFDE@kingspan.com W: kingspan.com

©2022 Kingspan Access Floors GmbH
Subject to technical changes and printing errors excepted!
kingspan-datasheet-pedestal-sw20-ssp6-en-de-v1 01/2023

